

Product Overview

The DC-SD-PRO3G is a grade 2 GSM alarm auto-dialler typically installed in fire & intruder applications. It has four alarm inputs to alert property owners directly, by SMS and voice call. Requires only power & SIM to operate.

◆ Fast Install

Installed and configured in minutes not hours.

◆ Online Setup

Management & configuration via SMS, app or web browser.

◆ Extremely reliable

Tried and tested mobile technology for over 12 years in global applications.

◆ Universally compatible

Monitor any type of alarm panel or use standalone with any sensor/s.



Features

- ◆ 4 Alarm users - to receive SMS/voice alarms.
- ◆ 4 inputs - for dual monitoring ie: leak/fault.
- ◆ 2 outputs - remote control outputs.
- ◆ Built-in auto-test event.
- ◆ Includes Sim car with 360 Texts
Sim car with 360 Texts
120 minutes
24mb data
120 minutes
24mb data
* valid for 12 months

Technical Specifications

- ◆ Power Supply (battery connected) - 13.8VDC - 15VDC ONLY.
- ◆ Power Supply (battery NOT connected) - 12-24VAC or 12-24VDC.
- ◆ Consumption - live: 250ma standby: 40ma.
- ◆ 3G GSM/GPRS module: 800/850/900/1900/2100 MHz (4G ready).
- ◆ Dimensions - 118 x 175 x 36 mm.
- ◆ Antenna type - SMA male.
- ◆ Weight - 500g.

Please Note

- ◆ The dialler must have a good signal to operate correctly – booster antenna available at extra cost if required.
- ◆ The dialler must be used in conjunction with the supplied SIM.
- ◆ Battery back up sold separately.